



Republic of the Philippines
Department of Education
 REGION VII - CENTRAL VISAYAS
 Schools Division of Cebu City

SUPPLEMENTAL BID BULLETIN
ADDENDUM NO./CORRIGENDUM NO. 01
September 12, 2024

This Addendum/Corrigendum No. 1 is issued to modify or amend item/s in the Bidding Documents for
Supply and Delivery of Learning Tools and Equipment (LTE) Science, Math and TVL Equipment, Packages for
Public Elementary, Junior and Senior High School of Schools Division of Cebu City
 with Project No. DepEd CCD-2024-21

This shall form an integral part of the part of the Bidding Documents

AS POSTED

Schedule of Requirements

Supply and Delivery of Learning Tools and Equipment (LTE) Science, Math and TVL Equipment, Packages for Public Elementary, Junior and Senior High School of Schools Division of Cebu City

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

Item Number	Description	Statement of Compliance
A. Supply and Delivery of Learning Tools and Equipment (LTE) Science Equipment (SME), Packages for Public Elementary, Junior and Senior High School of Schools Division of Cebu City		
1	LABORATORY DIGITAL BALANCE Specifications: EU Plug (with adaptor that will conform to PH) or US Plug; Voltage: 100-240V; Maximum weight: 20,000g; Accuracy Resolution: 0.1g; Background Light Color: White Display: LCD Unit: g, ct, oz, lb Battery: 1x9V Battery (Battery not included) Platform: Diameter: Approx. 13cm/5.1in Size: Approx. 27x19.5x6cm/10.4x7.7x2.4in Weight: Approx. 1940g/68.4oz Package List: 1x Balance Scale; 1x Instruction Manual; 1x Adapter Warranty: 1 year Qty: 16	
2	DIGITAL SOIL pH METER Specifications: digital pH Tester for Soil, Soil pH Test Kit for Indoor Potted Plants, Professional pH Meter for Soil and Water, Measuring Soil pH for Garden, Grass, Lawn, Greenhouse, Outdoor, Farming, Yard Use Style: Digital Soil pH Meter pH range: 0.0 – 14.0 pH Temp: 32.0 – 122.0 F Temp.ATC: 32.0 – 122.0 F Backlights: with backlights, can shut down backlights function Probe Type: spear probe with stainless steel dibber Calibration Point: 7.0/4.0/10.0 (can shift to point 6.86/4.00/9.18) Automatic Standby Time: 5 minutes Shut down: manual shut down by pressing ON/OFF button Operation Environment: 32.0 – 122.0°F 0.0 – 50.0°C Battery Type: 3*LR44 Alkaline Button Cell Battery Indicator: Low Battery Warning Product Size: 11.2*1.46*1.46in (Probe Length: 5.5 in) Bluetooth Version: Support Bluetooth 5.2 Version Bluetooth Opening: Long press "ON/OFF" button to open or shut down Bluetooth Application Field: All pH Testing for Soil and Water such as Indoor Potted Plants, Garden, Grass, Lawn, Greenhouse, Outdoor, Farming, Yard Use, Hydroponic Nutrients Solution, Rainwater, Well Water, Home Drinks and so on Warranty: 1 year Qty: 16 units	
3	ADULT HUMAN SKELETON MODEL ON A METAL VERTICAL ROD WITH 5 CASTERS STAND Specifications:	

	180 CM Human Skeleton Model Life Size Clear Bone Texture Include Nerve Roots Plastic Anatomica School Mannequin Qty: 10 Units	
B. Supply and Delivery of Learning Tools and Equipment (LTE) Math Equipment (SME), Packages for Public Elementary, Junior and Senior High School of Schools Division of Cebu City		
4	AUTO MEASUREMENT TOOL LINE LASER LEVEL Specifications: 12 /16 line irradiation, 360° without dead angle, far projection distance, high laser height, clear lines; Automatic self leveling function. Sound warning when beyond auto leveling scope; 360° rotating base with fine tuning knob. Thickened metal base and shockproof; Water/dust resistance; Wide applications for auxiliary tiles fixing, wall decoration, floor tiles fixing, stair handrails, furred ceiling, floor tile, plastering; Easy to carry. Line: 12 / 16 Lines; Light Colour: Green; Radium Rays: 360° (12 Line); Horizontal/Vertical Accuracy:±0.2mm/10m; Auto-leveling Range: ±3; Scope of work: About 25m in diameter; Operation Temperature Range:-5°C-50°C; Operating Hours: 4-5 hours; Protection Level: IP-54 Warranty: 1 year Qty: 59 Units	
B. Supply and Delivery of Learning Tools and Equipment (LTE) TVL Equipment (SME), Packages for Public Elementary, Junior and Senior High School of Schools Division of Cebu City		
5	ELECTRIC TESTER (VOM) MULTITESTER ANALOG HEAVY DUTY FUSED PROTECTED Specifications: <ul style="list-style-type: none"> • DC VOLTAGE – 100mV, 250mV, 2.5V, 10V, 50V, 250V, 1000V • AC Voltage – 10V, 50V, 250V, 750V • DC Null Meter - ±5V, ±25V • DC Current - 50µA, 2.5mA, 0.25A • Resistance: 2kΩ, 20kΩ, 200kΩ, 2MΩ, 200MΩ • Frequency Range 30Hz-10kHz ±3% on 10V ac range • 1 year Warranty Qty: 4 Units	
6	CLAMP METER (DIGITAL) DIGITAL AND MANUAL DC AND AC READING Specifications: <ul style="list-style-type: none"> • ACA – 60.00/600.0/1000A • ACV – 6.000/60.00/600.0/1000V • DCV – 6.000/60.00/600.0/1000V • Resistance–6.000k/60.00k/600.0k/6.000M/60.00mΩ • Capacitance – 60.00n/600.0n/6.000µ/600.0µ/6.000m/60.00mF • Continuity – Buzzer sounds below 30Ω Open Voltage: approx.. 1V or less • Detection of Electricity – Buzzer sounds, "*" is shown on LCD, and LED flickers, Detects ACV and EF of approx. 90V or more (50/60Hz) • Sampling rate – Approx. 3times/sec. • Bandwidth ACA 45-400Hz ACV 45Hz-1kHz • Display – 6000/999(Hz function) • Clamp diameter/Conductor size – Φ34mm/10×64mm • Battery life – Approx. 200hrs. • Size/Mass – H252×W85×D40mm/Approx. 360g Safety Standards – IEC61010 CAT.IV600V/CAT.III 100V Warranty: 1 year Qty: 5 Units	
7	HEAT GUN HEAVY DUTY 2000W 50-630 DEGREE CELSIUS Specifications: <ul style="list-style-type: none"> • *Rated input power: 2,000 W • *Weight: 0.65 kg • *Tool Dimension (width): 86mm • *Tool Dimension (length): 245mm • *Tool Dimension (height): 201mm • *Working Temperature: 50-630°C • *Airflow: 150 – 500 l/min • *Continuously variable temperature control: + • *Cold Stage, 50°C: - *Control, airflow: 3-stage Warranty: 1 year Qty: 5 Units	
8	GAS RANGE 4 BURNERS LPG GAS SOURCE STAINLESS MATERIAL 220-240v 50-60hz POWER SUPPLY Specifications: <ul style="list-style-type: none"> • *Electric Ignition • *4 Burners • *LPG Gas Source • *Stainless Material • *Panel Rotisserie • *Mechanical Control • *Double Glass Door • *Gas Oven • *220-240v/50-60Hz/ Power Supply • *Product Dimension: 600×570×810mm *Net Weight: 36kg Warranty: 1 year Qty: 3 Units	
9	STETHOSCOPE DELUXE STAINLESS STEEL Specifications: <ul style="list-style-type: none"> • Chest Piece: Aluminium Alloy • Tube: Polyvinyl Chloride (PVC) Plastic Contents • 1 PVC Tube. • 1 Dual-Head Chest Piece. 	

	<ul style="list-style-type: none"> • 2 Ear Tips. Regulations CE, FDA Manufacturer's Warranty Qty: 5 Units	
10	SPHYGMOMANOMETER DIGITAL Specifications: <ul style="list-style-type: none"> • 30 memory storage allows you to review the last 30 readings at the touch of a button • Cuff Wrapping Guide • Hypertension Indicators • Irregular Heartbeat Indicator • Intellisense Technology • Wrist Cuff (Medium to Large) 1.35 – 21.5cm pre-formed cuff which makes application fuss-free • LCD Display • Hard Carry Case • Power Source: Both AC/DC (powered both with Electricity and Battery) Manufacturer's Warranty Qty: 5 Units	
11	DIGITAL THERMOMETER (GUN) Specifications: <ul style="list-style-type: none"> • Instant, one-second reading • Non-contact temperature measurement • 3 measurement modes (forehead, surface, and room temperature) • Easy to hold design • Backlight provides visibility in the dark • Last reading displayed on the same screen as the current reading for easy comparison • Easily switch between Fahrenheit and Celsius • Memory feature recalls the last 25 readings • Silent mode • 2 Year Standard Warranty (4 if Registered Online) • Powered by AA or AAA battery Qty: 5 Units	
12	PAINT BRUSH ASSORTED SIZES SET Specifications: <ul style="list-style-type: none"> • Size: 1"-4" Color: Any Color Qty: 2 Sets	
13	ELECTRIC BLOWER Specifications: <ul style="list-style-type: none"> • Lock-on button for one hand control and user safety • 600W powerful motor for higher tool performance • 2 Tools in 1: Blower and vacuum cleaner • Light and compact design for ease of handling • Optimized fan structure for better air flow • Variable speed option for easy control of airflow • Rubber nozzle for greater flexibility during work • Suction mode used in restricted application areas • Length (mm) – 470 • Height (mm) – 225 • Weight (kg) – 1.7 • Power Input (W) – 600 • Air Flow (m3/min) – 3.5 • No Load Speed (rpm) – 16000 Manufacturer's Warranty Qty: 4 Units	

MANNER OF PAYMENT

The Supplier shall bill DepEd Cebu City Division upon delivery of all requested goods/items. For this purpose, the Supplier shall issue Delivery Receipt. Non-compliance thereon gives DepEd Cebu City Division the right to disallow payment of the bill; and any falsehood or misrepresentation in the certification shall constitute breach of the Contract, which is a ground for termination thereof.

I hereby commit to comply with all the above requirements.

 Name of Company/Bidder

 Signature over Printed Name of Bidder

 Date

AS CORRECTED

Section VII. Technical Specifications

TECHNICAL SPECIFICATIONS

Supply and Delivery of Learning Tools and Equipment (LTE) Science, Math and TVL Equipment, Packages for Public Elementary, Junior and Senior High School of Schools Division of Cebu City

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

Item Number	Description	Statement of Compliance
A. Supply and Delivery of Learning Tools and Equipment (LTE) Science Equipment (SME), Packages for Public Elementary, Junior and Senior High School of Schools Division of Cebu City		
1	<p>LABORATORY DIGITAL BALANCE Specifications: EU Plug (with adaptor that will conform to PH) or US Plug; Voltage:100-240V; Maximum weight: 20,000g; Accuracy Resolution: 0.1g; Background Light Color: White Display: LCD Unit: g, ct, oz, lb Battery: 1x9V Battery (Battery not included) Platform: Diameter: Approx. 13cm/5.1in Size: Approx. 27x19.5x6cm/10.4x7.7x2.4in Weight: Approx. 1940g/68.4oz Package List: 1x Balance Scale; 1x Instruction Manual; 1x Adapter Warranty: 1 year Qty: 16</p>	
2	<p>DIGITAL SOIL pH METER Specifications: digital pH Tester for Soil, Soil pH Test Kit for Indoor Potted Plants, Professional pH Meter for Soil and Water, Measuring Soil pH for Garden, Grass, Lawn, Greenhouse, Outdoor, Farming, Yard Use Style: Digital Soil pH Meter pH range: 0.0 – 14.0 pH Temp: 32.0 – 122.0 F Temp.ATC: 32.0 – 122.0 F Backlights: with backlights, can shut down backlights function Probe Type: spear probe with stainless steel dibber Calibration Point: 7.0/4.0/10.0 (can shift to point 6.86/4.00/9.18) Automatic Standby Time: 5 minutes Shut down: manual shut down by pressing ON/OFF button Operation Environment: 32.0 – 122.0°F 0.0 – 50.0°C Battery Type: 3*LR44 Alkaline Button Cell Battery Indicator: Low Battery Warning Product Size: 11.2*1.46*1.46in (Probe Length:5.5 in) Bluetooth Version: Support Bluetooth 5.2 Version Bluetooth Opening: Long press "ON/OFF" button to open or shut down Bluetooth Application Field: All pH Testing for Soil and Water such as Indoor Potted Plants, Garden, Grass, Lawn, Greenhouse, Outdoor, Farming, Yard Use, Hydroponic Nutrients Solution, Rainwater, Well Water, Home Drinks and so on Warranty: 1 year Qty: 16 units</p>	
3	<p>ADULT HUMAN SKELETON MODEL ON A METAL VERTICAL ROD WITH 5 CASTERS STAND Specifications: 180 CM Human Skeleton Model Life Size Clear Bone Texture Include Nerve Roots Plastic Anatomica School Mannequin Qty: 10 Units</p>	
B. Supply and Delivery of Learning Tools and Equipment (LTE) Math Equipment (SME), Packages for Public Elementary, Junior and Senior High School of Schools Division of Cebu City		
4	<p>AUTO MEASUREMENT TOOL LINE LASER LEVEL Specifications: 12 /16 line irradiation, 360° without dead angle, far projection distance, high laser height, clear lines; Automatic self leveling function. Sound warning when beyond auto leveling scope; 360° rotating base with fine tuning knob. Thickened metal base and shockproof; Water/dust resistance; Wide applications for auxiliary tiles fixing, wall decoration, floor tiles fixing, stair handrails, furred ceiling, floor tile, plastering; Easy to carry. Line: 12 / 16 Lines; Light Colour: Green; Radium Rays: 360° (12 Line); Horizontal/Vertical Accuracy:±0.2mm/10m; Auto-leveling Range: ±3; Scope of work: About 25m in diameter; Operation Temperature Range:-5°C~50°C; Operating Hours: 4-5 hours; Protection Level: IP-54 Warranty: 1 year Qty: 59 Units</p>	
B. Supply and Delivery of Learning Tools and Equipment (LTE) TVL Equipment (SME), Packages for Public Elementary, Junior and Senior High School of Schools Division of Cebu City		

5	<p>ELECTRIC TESTER (VOM) MULTITESTER ANALOG HEAVY DUTY FUSED PROTECTED</p> <p>Specifications:</p> <ul style="list-style-type: none"> • DC VOLTAGE – 100mV, 250mV, 2.5V, 10V, 50V, 250V, 1000V • AC Voltage – 10V, 50V, 250V, 750V • DC Null Meter - ±5V, ±25V • DC Current - 50µA, 2.5mA, 0.25A • Resistance: 2kΩ, 20kΩ, 200kΩ, 2MΩ, 200MΩ • Frequency Range 30Hz-10kHz ±3% on 10V ac range • 1 year Warranty <p>Qty: 4 Units</p>	
6	<p>CLAMP METER (DIGITAL) DIGITAL AND MANUAL DC AND AC READING</p> <p>Specifications:</p> <ul style="list-style-type: none"> • ACA – 60.00/600.0/1000A • ACV – 6.000/60.00/600.0/1000V • DCV – 6.000/60.00/600.0/1000V • Resistance – 6.000k/60.00k/600.0k/6.000M/60.00mΩ • Capacitance – 60.00n/600.0n/6.000µ/600.0µ/6.000m/60.00mF • Continuity – Buzzer sounds below 30Ω Open Voltage: approx.. 1V or less • Detection of Electricity – Buzzer sounds, "-" is shown on LCD, and LED flickers, Detects ACV and EF of approx. 90V or more (50/60Hz) • Sampling rate – Approx. 3times/sec. • Bandwidth ACA 45-400Hz ACV 45Hz-1kHz • Display – 6000/999(Hz function) • Clamp diameter/Conductor size – φ34mm/10×64mm • Battery life – Approx. 200hrs. • Size/Mass – H252×W85×D40mm/Approx. 360g <p>Safety Standards – IEC61010 CAT.IV600V/CAT.III 100V Warranty: 1 year</p> <p>Qty: 5 Units</p>	
7	<p>HEAT GUN HEAVY DUTY 2000W 50-630 DEGREE CELSIUS</p> <p>Specifications:</p> <ul style="list-style-type: none"> • *Rated input power: 2,000 W • *Weight: 0.65 kg • *Tool Dimension (width): 86mm • *Tool Dimension (length): 245mm • *Tool Dimension (height): 201mm • *Working Temperature: 50-630°C • *Airflow: 150 – 500 l/min • *Continuously variable temperature control: + • *Cold Stage, 50°C: - <p>*Control, airflow: 3-stage Warranty: 1 year</p> <p>Qty: 5 Units</p>	
8	<p>GAS RANGE 4 BURNERS LPG GAS SOURCE STAINLESS MATERIAL 220-240v 50-60hz POWER SUPPLY</p> <p>Specifications:</p> <ul style="list-style-type: none"> • *Electric Ignition • *4 Burners • *LPG Gas Source • *Stainless Material • *Panel Rotisserie • *Mechanical Control • *Double Glass Door • *Gas Oven • *220-240v/50-60Hz/ Power Supply • *Product Dimension: 600×570×810mm <p>*Net Weight: 36kg Warranty: 1 year</p> <p>Qty: 3 Units</p>	
9	<p>STETHOSCOPE DELUXE STAINLESS STEEL</p> <p>Specifications:</p> <ul style="list-style-type: none"> • Chest Piece: Aluminium Alloy • Tube: Polyvinyl Chloride (PVC) Plastic Contents • 1 PVC Tube. • 1 Dual-Head Chest Piece. • 2 Ear Tips. <p>Regulations CE, FDA Manufacturer's Warranty</p> <p>Qty: 5 Units</p>	
10	<p>SPHYGMOMANOMETER DIGITAL</p> <p>Specifications:</p> <ul style="list-style-type: none"> • 30 memory storage allows you to review the last 30 readings at the touch of a button • Cuff Wrapping Guide • Hypertension Indicators • Irregular Heartbeat Indicator • Intellisense Technology • <i>Wrist Cuff (Medium to Large)</i> 1.35 – 21.5cm pre-formed cuff which makes application fuss-free • LCD Display • Hard Carry Case • Power Source: Both AC/DC (powered both with Electricity and Battery) 	

	Manufacturer's Warranty Qty: 5 Units	
11	DIGITAL THERMOMETER (GUN) Specifications: <ul style="list-style-type: none"> • Instant, one-second reading • Non-contact temperature measurement • 3 measurement modes (forehead, surface, and room temperature) • Easy to hold design • Backlight provides visibility in the dark • Last reading displayed on the same screen as the current reading for easy comparison • Easily switch between Fahrenheit and Celsius • Memory feature recalls the last 25 readings • Silent mode • 2 Year Standard Warranty (4 if Registered Online) • Powered by AA or AAA battery Qty: 5 Units	
12	PAINT BRUSH ASSORTED SIZES SET Specifications: <ul style="list-style-type: none"> • Size: 1"-4" • Color: Any Color Qty: 2 Sets	
13	ELECTRIC BLOWER Specifications: <ul style="list-style-type: none"> • Lock-on button for one hand control and user safety • 600W powerful motor for higher tool performance • 2 Tools in 1: Blower and vacuum cleaner • Light and compact design for ease of handling • Optimized fan structure for better air flow • Variable speed option for easy control of airflow • Rubber nozzle for greater flexibility during work • Suction mode used in restricted application areas • Length (mm) – 470 • Height (mm) – 225 • Weight (kg) – 1.7 • Power Input (W) – 600 • Air Flow (m3/min) – 3.5 • No Load Speed (rpm) – 16000 • Manufacturer's Warranty Qty: 4 Units	

MANNER OF PAYMENT

The Supplier shall bill DepEd Cebu City Division upon delivery of all requested goods/items. For this purpose, the Supplier shall issue Delivery Receipt. Non-compliance thereon gives DepEd Cebu City Division the right to disallow payment of the bill; and any falsehood or misrepresentation in the certification shall constitute breach of the Contract, which is a ground for termination thereof.

I hereby commit to comply with all the above requirements.

Name of Company/Bidder

Signature over Printed Name of Bidder

Date

ADOLF P. AGUILAR
BAC Chairman